

INSTALLATION INSTRUCTIONS:

- 1. Remove center screw from cover plate of duplex wall outlet.
- 2. Plug converter into the wall outlet and secure with the center screw provided.
- 3. Unit is ready to use.

FEATURE OPTION

<input type="checkbox"/>	WITH COAX LINE PROTECTION	<input checked="" type="checkbox"/>	WITH PHONE LINE PROTECTION	<input type="checkbox"/>	WITH BNC NETWORK PROTECTION
--------------------------	------------------------------	-------------------------------------	-------------------------------	--------------------------	-----------------------------------

AC POWER LINE SURGE HANDLING SPECIFICATIONS:

POWER RATING.....15A, 125VAC. 1875 WATTS
 MAXIMUM SPIKE ENERGY DISSIPATION.....90+90+90 JOULES
 MAXIMUM SPIKE VOLTAGE.....6000 VOLTS
 MAXIMUM SPIKE CURRENT.....4,500A
 MAXIMUM CLAMPING VOLTAGE.....330V
 CLAMPING RESPONSE TIME.....UNDER 1 NANO-SECOND
 MEET UL SPEC# 1449 FOR SURGE SUPPRESSORS

CAUTION: TO REDUCE THE RISK OF ELECTRIC SHOCK DISCONNECT POWER TO THE RECEPTACLE BEFORE INSTALLING OR REMOVING THE UNIT. WHEN REMOVING RECEPTACLE COVER SCREW, COVER MAY FALL ACROSS PLUG PINS OR RECEPTACLE MAY BE DISLODGED. USE ONLY WITH DUPLEX RECEPTACLE HAVING CENTER SCREW. SECURE UNIT IN PLACE WITH SCREW PROVIDED. THE UNIT SHOULD BE PLUGGED INTO A PARALLEL DUPLEX RECEPTACLE.

191533 REV 0

INSTALLATION INSTRUCTIONS:

- 1. Remove center screw from cover plate of duplex wall outlet.
- 2. Plug converter into the wall outlet and secure with the center screw provided.
- 3. Unit is ready to use.

FEATURE OPTION

<input type="checkbox"/>	WITH COAX LINE PROTECTION	<input checked="" type="checkbox"/>	WITH PHONE LINE PROTECTION	<input type="checkbox"/>	WITH BNC NETWORK PROTECTION
--------------------------	------------------------------	-------------------------------------	-------------------------------	--------------------------	-----------------------------------

AC POWER LINE SURGE HANDLING SPECIFICATIONS:

POWER RATING.....15A, 125VAC. 1875 WATTS
 MAXIMUM SPIKE ENERGY DISSIPATION.....90+90+90 JOULES
 MAXIMUM SPIKE VOLTAGE.....6000 VOLTS
 MAXIMUM SPIKE CURRENT.....4,500A
 MAXIMUM CLAMPING VOLTAGE.....330V
 CLAMPING RESPONSE TIME.....UNDER 1 NANO-SECOND
 MEET UL SPEC# 1449 FOR SURGE SUPPRESSORS

CAUTION: TO REDUCE THE RISK OF ELECTRIC SHOCK DISCONNECT POWER TO THE RECEPTACLE BEFORE INSTALLING OR REMOVING THE UNIT. WHEN REMOVING RECEPTACLE COVER SCREW, COVER MAY FALL ACROSS PLUG PINS OR RECEPTACLE MAY BE DISLODGED. USE ONLY WITH DUPLEX RECEPTACLE HAVING CENTER SCREW. SECURE UNIT IN PLACE WITH SCREW PROVIDED. THE UNIT SHOULD BE PLUGGED INTO A PARALLEL DUPLEX RECEPTACLE.

191533 REV 0